



## Field Concentration in Hydrogel-Elastomer Devices

Vaicekauskaite, Justina; Yang, Canhui ; Skov, Anne Ladegaard; Suo, Zhigang

*Publication date:*  
2019

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*

Vaicekauskaite, J., Yang, C., Skov, A. L., & Suo, Z. (2019). Field Concentration in Hydrogel-Elastomer Devices. Abstract from 9th International Conference on Electromechanically Active Polymer (EAP) Transducers & Artificial Muscles (EuroEAP 2019), Dresden, Germany.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Field Concentration in Hydrogel-Elastomer Devices

Justina Vaicekauskaitė<sup>1, 2</sup>, Canhui Yang<sup>2</sup>, Anne Ladegaard Skov<sup>1</sup>, Zhigang Suo<sup>2,\*</sup>

<sup>1</sup>*Danish Polymer Center, Department of Chemical and Biochemical Engineering, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark*

<sup>2</sup>*John A. Paulson School of Engineering and Applied Sciences, Kavli Institute for Bionano Science and Technology, Harvard University, MA, 02138, USA. E-mail: suo@seas.harvard.edu*

Dielectric elastomer actuators (DEAs) are promising for many applications owing to their remarkable merits such as large deformation, fast response, high efficiency, low cost, and light weight. Recently, hydrogels have been used to activate DEAs. In these devices, hydrogels serve as the stretchable transparent electrodes and elastomers serve as the stretchable transparent dielectrics. However, the emerging of such hydrogel-elastomer devices has posed many challenges due to the distinct nature of hydrogel and elastomer. Intensive researches are taking place to learn more about hydrogel-elastomer systems. In this work, we study field concentration and its influences on hydrogel-elastomer devices. We fabricate a DEA by using polyacrylamide hydrogels containing lithium chloride as the electrodes and polydimethylsiloxane elastomer as the dielectrics. We find that most devices fail on the side of electrode, where field concentration is the strongest. We observe salting out phenomenon and local temperature increase, as well as plasma during the experiments. We hypothesize that electric field concentrates at the edges of hydrogels, causing the surrounding air to break down. Which produces plasma that heats up hydrogels thus leading to the salting out. We note that the breakdown of air helps dissipate energy into the air and protects the DEAs.